


Features

- Knurled nut suitable for tool mounting
- Mechanical detent for vibration protection
- Gold-plated and machined contacts


Technical data

Number of pins	3	4
Electrical data		
Operating voltage U_b	Max. 60 V AC/DC	Max. 30 V AC/DC
Testing voltage	> 1500 V_{eff} AC	
Operating current	Max. 3 A	
Volume resistance	< 5 m Ω	
Ambient conditions		
Ambient temperature	-40 ... 90 °C for body Information on cable quality can be found beginning on page 10	
Degree of pollution	3	
Mechanical data		
Contact elements	Spring-loaded contact sockets	
Degree of protection	IP67	
Material		
Contacts	CuSn / Au	
Contact surface	Au	
Body	TPU, green	
Coupling nut	Die-cast zinc	

Dimensions



Electrical connection



Order codes

Cable lengths in m
0.3 to 50

Order code structure: V . . - G M - M -

Cable quality

- PVC	PVC, gray (0.25 mm ²)	V3	V31
BK PVC-U	PVC, UL-approved, black (0.34 mm ²)	○	○
YE PVC-U	PVC, UL-approved, yellow (0.34 mm ²)	○	○
- PUR	PUR, halogen-free, gray (0.25 mm ²)	●	●
BK PUR-U	PUR, halogen-free, UL-approved, black (0.34 mm ²)	○	○
YE PUR-U	PUR, halogen-free, UL-approved, yellow (0.34 mm ²)	○	○

● Standard, cable lengths of 2m, 5 m and 10 m available in stock
○ Available, minimum order quantity applies in some cases
- Not available

Number of pins

V3 3-pin
V31 4-pin



Features

- Built-in LED, as operating and function indicator
- Knurled nut suitable for tool mounting
- Mechanical detent for vibration protection
- Gold-plated and machined contacts

Technical data

Number of pins	3 (E2)	4 (A2)
Display/controls		
Green LED	Operating display	
Yellow LED	NO contact function display	
Electrical data		
Operating voltage U_b	Max. 24 V DC \pm 15%	
Operating current	Max. 3 A	
Volume resistance	< 5 m Ω	
Ambient conditions		
Ambient temperature	-40 ... 90 °C for body Information on cable quality can be found beginning on page 10	
Degree of pollution	3	
Mechanical data		
Contact elements	Spring-loaded contact sockets	
Degree of protection	IP67	
Material		
Contacts	CuSn / Au	
Contact surface	Au	
Body	TPU, transparent	
Coupling nut	Die-cast zinc	

Sensor-actuator cable

Field-attachable connectors


Junction blocks

Sensor-actuator splitters


Sensor-actuator receptacles

Data connectors

Dimensions



Electrical connection



Order codes

Cable lengths in m
0.3 to 50

V . . - G M - M -

Cable quality

-	PVC	PVC, gray (0.25 mm ²)	V3	V31
BK	PVC-U	PVC, UL-approved, black (0.34 mm ²)	○	○
YE	PVC-U	PVC, UL-approved, yellow (0.34 mm ²)	○	○
-	PUR	PUR, halogen-free, gray (0.25 mm ²)	●	●
BK	PUR-U	PUR, halogen-free, UL-approved, black (0.34 mm ²)	○	○
YE	PUR-U	PUR, halogen-free, UL-approved, yellow (0.34 mm ²)	○	○

● Standard, cable lengths of 2 m, 5 m and 10 m available in stock
○ Available, minimum order quantity applies in some cases
- Not available

Number of pins

V3	E2	3-pin
V31	A2	4-pin




Features

- Built-in LED, as operating and function indicator
- Knurled nut suitable for tool mounting
- Mechanical detent for vibration protection
- Gold-plated and machined contacts


Technical data

Number of pins	3 (E2)	4 (A2)
Display/controls		
Green LED	Operating display	
Yellow LED	NO contact function display	
Electrical data		
Operating voltage U_B	Max. 24 V DC \pm 15%	
Operating current	Max. 3 A	
Volume resistance	< 5 m Ω	
Ambient conditions		
Ambient temperature	-40 ... 90 °C for body Information on cable quality can be found beginning on page 10	
Degree of pollution	3	
Mechanical data		
Contact elements	Spring-loaded contact sockets	
Degree of protection	IP67	
Material		
Contacts	CuSn / Au	
Contact surface	Au	
Body	TPU, transparent	
Coupling nut	Die-cast zinc	

Dimensions



Electrical connection



Order codes

Cable lengths in m
0.3 to 50

Cable quality

- PVC	PVC, gray (0.25 mm ²)	V3	V31
BK PVC-U	PVC, UL-approved, black (0.34 mm ²)	○	○
YE PVC-U	PVC, UL-approved, yellow (0.34 mm ²)	○	○
- PUR	PUR, halogen-free, gray (0.25 mm ²)	●	●
BK PUR-U	PUR, halogen-free, UL-approved, black (0.34 mm ²)	○	○
YE PUR-U	PUR, halogen-free, UL-approved, yellow (0.34 mm ²)	○	○

● Standard, cable lengths of 2 m, 5 m and 10 m available in stock
○ Available, minimum order quantity applies in some cases
- Not available

Number of pins

V3	E2	3-pin
V31	A2	4-pin